

Diesel Fuel Service Cart



A 3-in-1 Diesel Fuel Service Cart that efficiently removes water and bacterial growth from diesel fuel reducing the possibility of engine or fuel system damage.

The cart is equipped with a Separ Filter fuel/water separator that cleans diesel by circulating and filtering the fuel. This prevents maintenance problems and makes sure your systems are kept ready for emergency situations and daily operations.

- Lightweight and designed with truck skids for easy loading and operation
- The most compact cart easily fits through building doorways
- Can run unattended
- Has safety shutdown, alarms for filter and water and maintenance alerts
- Removes 99.9% water and 99% bacterial growth detrimental to pumps and injectors
- For tanks up to 10,000 gallons

Applications

- Fleet Maintenance
- Portable Cleaning
- Boatyards
- Fuel Polishing Services
- Backup Power Maintenance
- Field Maintenance
- Above/Below Ground Tanks
- Farm Equipment
- Equipment Belly Tanks
- Fuel Dispensing

3-in-1 Portable System

- 1** Polish the storage tank
Fuel stored more than 3 months begins to degrade
- 2** Polish when dispensing
Transfer clean fuel when delivering from unreliable sources
- 3** Polish the engine tank
Equipment is ready when unused for a period of time



REVERSO

Reverso Pumps, Inc.
www.reversopumps.com
contact@reversopumps.com
Ph: (954) 522-0882



Shown with optional flow meter.

Basic Features

- Hose - 15 ft suction and discharge
- Separ Filter SWK-2000/40MK
- 30 micron paper element
- Electronic control box with 0 to 5 hour timer
- LED indicators for element replacement and backflushing
- Drip pan - easy to remove for cleaning
- Vacuum gauge
- Safety shutdown and alarm for clogged filter and water
- Truck skids
- Hose hanger
- Strainer valve on suction side

Optional Features

- Manual nozzle
- Flow meter
- Variable length pickup/discharge tube
- 60 micron stainless steel element
- 10 micron paper element

Flow Rate	630 GPH / 2,400 LPH	
Voltage	120V / 60 Hz	
Amp. Draw	3.4A / 120V	
Pump Type	Vane	
Self-Priming	6.7 ft / 2m (wet gears)	
Dimensions	Width	21.5" / 546 mm
	Height	50.5" / 1,282 mm
	Depth	22.9" / 581 mm
Weight	105 lbs / 47.6 kg	

SWK-2000/40MK from Separ Filter



The Diesel Fuel Service Cart features the SWK-2000/40MK. The Separ patented filtration is achieved by 5 separate stages to remove water and particulate from diesel fuel. The end result is clean, reliable fuel delivered to the engine or storage tank.

- Small filter size keeps the cart lightweight in comparison to competitor brands with the same flow rate
- Separates most debris and large particles before they reach the element, thereby extending element life
- Backflush capability reduces frequency of element replacements
- Metal filter housing and bowl
- Water level contacts



REVERSO

Reverso Pumps, Inc.
 www.reversopumps.com
 contact@reversopumps.com
 Ph: (954) 522-0882