

# Vane Pump 620

Durable, self-priming, self-ventilated vane pump for diesel fuel only. Bypass and 100 micron filter is built into pump. Compact pump is ideal for dispensing or transferring diesel fuel. Suitable for continuous use with thermal motor and overload protection.

## Basic Features

- Self-priming
- IP55 rated
- Equipped with On/off switch
- Available in 110V
- One-direction flow
- On/off switch



## Technical Specifications

<b>Flow Rate</b>	10 GPM / 37.9 LPM	
<b>Voltage</b>	110V or 220V	
<b>Ports</b>	1" Female NPT	
<b>Max. Suction Lift</b>	11.5 ft / 3.5m with foot valve above liquid level	
<b>Pressure</b>	29 psi / 2 bar / 220V	
<b>HP</b>	1/2	
<b>Watts</b>	520 / 110V 350 / 220V	
<b>Amperage</b>	4A / 110V 2.5A / 220V	
<b>Pump Type</b>	Vane	
<b>Body</b>	Cast-iron	
<b>Seal</b>	Mechanical	
<b>Motor</b>	Induction	
<b>Self-Priming</b>	6.7 ft / 2 m (wet gears)	
<b>Rated</b>	IP55	
<b>Dimensions</b>	A	8.6" / 218 mm
	B	5.9" / 150 mm
	C	6.8" / 173 mm

