

# Gear Pump 211

The GP-211 is a convenient gear pump for transferring diesel, oil or water. Fluid can be pulled up to 5 ft self-priming and is recommended for horizontal distances up to 10 ft. Flow direction is reversible and designed for discontinuous use. Optional switches are available.

## Basic Features

- Self-priming
- IP65 rated
- Available in 12V and 24V



## Technical Specifications

<b>Flow Rate</b>	1.5 GPM / 5.7 LPM	
<b>Inlet/Outlet</b>	3/8" Male NPT	
<b>Voltage</b>	12V or 24V	
<b>Duty Cycle</b>	30 min.	
<b>Self-Priming</b>	5 ft / 1.5 m (wet gears)	
<b>Max. Work Pressure</b>	21.7 psi / 1.5 bar	
<b>Max. Work Temperature</b>	140°F / 60°C	
<b>Max. Amp. Draw</b>	6A / 12V, 3A / 24V	
<b>Fuse</b>	10A / 12V, 5A / 24V	
<b>Pump Type</b>	Gear	
<b>Body</b>	Bronze	
<b>Gears</b>	Helical bronze	
<b>Shaft</b>	Stainless steel	
<b>Seal</b>	Fluoroelastomer lip seal	
<b>Rated</b>	IP65	
<b>Dimensions GP-211</b>	A	5.5" / 140 mm
	B	3.9" / 99 mm
	C	3" / 76 mm

