

# GP-900 Series

Self-priming, positive displacement gear pump ideal for oil and diesel fuel. Compact and durable. Self-lubricating bearings and close tolerance design for consistent performance.

## Optional Feature

- Reversing (R) switch, base, and fuse assembly



Pump and base



Switch, base, and fuse assembly

## Technical Specifications

<b>Flow Rate</b>	2 GPM / 7.5 LPM / 12V 5.6 GPM / 21.1 LPM / 24V	
<b>Ports</b>	5/8" Male Flare	
<b>Voltage</b>	12V, 24V	
<b>Breaker</b>	20A / 12V, 10A / 24V	
<b>Lift</b>	20 ft / 6.1m (water)	
<b>Gears</b>	Bronze	
<b>Shaft</b>	Stainless steel	
<b>Seal</b>	Buna lip seal	
<b>Bearings</b>	Carbon-graphite	
<b>Dimensions</b> GP-9012 GP-9024	A	15" / 381 mm
	B	5.8" / 149 mm
	C	6.8" / 173 mm
<b>Dimensions</b> GP-9012R GP-9024R	A	18.5" / 470 mm
	B	7.75" / 197 mm
	C	7.75" / 197 mm
<b>Shipping Weight</b>	31 lbs / 14 kg	

Pressure (psi)	12V Flow (GPM)	12V Amp (A)	24V Flow (GPM)	24V Amp (A)
5	2.8	4.5	5.9	5.9
10	2.7	5.5	5.8	6.8
15	2.7	6.4	5.8	7.6
20	2.6	7.4	5.7	8.4
25	2.5	8.7	5.6	9.1
30	2.4	9.5		
35	2.3	10.7		
40	2.2	12.4		
45	2.1	13.4		
50	2.1	14.4		
55	2	15.7		

