

GP-900 Series

Self-priming, positive displacement gear pump ideal for oil and diesel fuel. Compact and durable. Self-lubricating bearings and close tolerance design for consistent performance.

Optional Feature

- Reversing (R) switch, base, and fuse assembly



Pump and base



Switch, base, and fuse assembly

Technical Specifications

Flow Rate	2 GPM / 7.5 LPM / 12V 5.6 GPM / 21.1 LPM / 24V	
Ports	5/8" Male Flare	
Voltage	12V, 24V	
Breaker	20A / 12V, 10A / 24V	
Lift	20 ft / 6.1m (water)	
Gears	Bronze	
Shaft	Stainless steel	
Seal	Buna lip seal	
Bearings	Carbon-graphite	
Dimensions GP-9012 GP-9024	A	15" / 381 mm
	B	5.8" / 149 mm
	C	6.8" / 173 mm
Dimensions GP-9012R GP-9024R	A	18.5" / 470 mm
	B	7.75" / 197 mm
	C	7.75" / 197 mm
Shipping Weight	31 lbs / 14 kg	

Pressure (psi)	12V Flow (GPM)	12V Amp (A)	24V Flow (GPM)	24V Amp (A)
5	2.8	4.5	5.9	5.9
10	2.7	5.5	5.8	6.8
15	2.7	6.4	5.8	7.6
20	2.6	7.4	5.7	8.4
25	2.5	8.7	5.6	9.1
30	2.4	9.5		
35	2.3	10.7		
40	2.2	12.4		
45	2.1	13.4		
50	2.1	14.4		
55	2	15.7		

