

Diesel Fuel Service Cart



A 3-in-1 Diesel Fuel Service Cart that efficiently removes water and bacterial growth from diesel fuel reducing the possibility of engine or fuel system damage.

The cart is equipped with a Separ Filter fuel/water separator that cleans diesel by circulating and filtering the fuel. This prevents maintenance problems and makes sure your systems are kept ready for emergency situations and daily operations.

- Lightweight and designed with truck skids for easy loading and operation
- The most compact cart easily fits through building doorways
- Can run unattended
- Has safety shutdown, alarms for filter and water and maintenance alerts
- Removes 99.9% water and 99% bacterial growth detrimental to pumps and injectors
- For tanks up to 10,000 gallons

Applications

- Fleet Maintenance
- Portable Cleaning
- Boatyards
- Fuel Polishing Services
- Backup Power Maintenance
- Field Maintenance
- Above/Below Ground Tanks
- Farm Equipment
- Equipment Belly Tanks
- Fuel Dispensing

3-in-1 Portable System

- 1** Polish the storage tank
Fuel stored more than 3 months begins to degrade
- 2** Polish when dispensing
Transfer clean fuel when delivering from unreliable sources
- 3** Polish the engine tank
Equipment is ready when unused for a period of time



REVERSO

Reverso Pumps LLC
www.reversopumps.com
contact@reversopumps.com
Ph: (954) 522-0882



Shown with optional flow meter.

Basic Features

- Hose - 15 ft suction and discharge
- Separ Filter SWK-2000/40MK
- 30 micron paper element
- Control with 0 to 5 hour timer
- LED indicators for element replacement and backflushing
- Drip pan - easy to remove for cleaning
- Vacuum gauge
- Safety shutdown and alarm for clogged filter and water
- Truck skids
- Hose hanger
- Strainer valve on suction side

Optional Accessories

- Manual nozzle
- Flow meter
- Variable length pickup/discharge tube
- 60 micron stainless steel element
- 10 micron paper element

| | | |
|---------------------|-------------------------|------------------|
| Flow Rate | 630 GPH / 2,400 LPH | |
| Voltage | 120V / 60 Hz | |
| Amp. Draw | 3.4A / 120V | |
| Pump Type | Vane | |
| Self-Priming | 6.7 ft / 2m (wet gears) | |
| Dimensions | Width | 21.5" / 546 mm |
| | Height | 50.5" / 1,282 mm |
| | Depth | 22.9" / 581 mm |
| Weight | 105 lbs / 47.6 kg | |

Begin Fuel Cleaning With A Basic Cart Or Use A Starter Pack:

Starter Pack

- Diesel Fuel Service Cart
- Installed flow meter
- Installed manual nozzle and holder
- (1) Seal kit for Separ Filter
- (1) 60 micron stainless steel element
- (1) 10 micron paper element

REVERSO

Reverso Pumps LLC
www.reversopumps.com
contact@reversopumps.com
 Ph: (954) 522-0882